

Technical Bulletin



COVERED HOPPER CAR

HTH Covered Hopper Car

The HTH covered hopper car is a three-unit articulated, ideal for grains, sugar, bran and fertilizer transport.

Provided with bogies Motion Control, Coupler, E type and truck-mounted brake system.

The car is unloaded by rapid discharge system. The system can be Pneumatic or Manual.

The car body is fabricated in high-strength low-alloy structural steel.

DIMENSIONS (APPROXIMATE)

LENGTH, OVER TRUCK CENTERS	6.950 MM	WIDTH, EXTREME	3.130 MM
LENGTH, OVER STRIKERS	21.178 MM	JOURNAL SIZE	6" X 11"
LENGTH, OVER COUPLERS	24.978 MM	TRACK GAUGE	1,00 M
HEIGHT, EXTREME	4.100 MM		

WEIGHT / CAPACITY (ESTIMATED)

CURVE NEGOTIABILITY RADIUS

LIGHT WEIGHT	42.700 KG	CURVE NEGOTIABILITY	60 M
GROSS RAIL LOAD	194.200 KG		
LOAD LIMIT	151.500 KG		
CUBIC CAPACITY	196,8 M ³		

These general dimensions are representative and subject to change without notice as required by customer specifications or design improvements by Greenbrier Maxion.

Rua 10 S/N – Sítio São João
Jd. São Camilo | Hortolândia | SP
CEP: 13184-902
Tel.: (55 19) 2118-2000

www.gbm.com.br

