

## Technical Bulletin



### COVERED HOPPER CAR

### HTT Covered Hopper Car

The HTT covered hopper car is ideal for grains, sugar, bran and fertilizer transport.

Provided with Ride Control bogies, with 6 ½" x 9" journals, Coupler, F type and conventional brake system.

The car is unloaded by rapid discharge system.

The car body is fabricated in high-strength low-alloy structural steel.

#### DIMENSIONS (APPROXIMATE)

LENGTH, OVER TRUCK CENTERS	11.970 MM	WIDTH, EXTREME	3.244 MM
LENGTH, OVER STRIKERS	15.000 MM	JOURNAL SIZE	6 ½" X 9"
LENGTH, OVER COUPLERS	15.800 MM	TRACK GAUGE	1,60 M
HEIGHT, EXTREME	4.626 MM		

#### WEIGHT / CAPACITY (ESTIMATED) | CURVE NEGOTIABILITY RADIUS

LIGHT WEIGHT	28.300 KG	CURVE NEGOTIABILITY	100 M
GROSS RAIL LOAD	130.000 KG		
LOAD LIMIT	101.700 KG		
CUBIC CAPACITY	143 M <sup>3</sup>		

These general dimensions are representative and subject to change without notice as required by customer specifications or design improvements by Greenbrier Maxion.

Rua 10 S/N – Sítio São João  
 Jd. São Camilo | Hortolândia | SP  
 CEP: 13184-902  
 Tel.: (55 19) 2118-2000

[www.gbmx.com.br](http://www.gbmx.com.br)

